

# HuneTec H200

The HuneTec H200 2Way gives you messaging power and information management in a sleek PDA-sized package

- ▶ Small and lightweight.
- ▶ Large backlit display shows approximately seven, 25-character lines.
- ▶ Lighted QWERTY keyboard for fast message and information entry.
- ▶ Address book holds more than 200 contacts.

- ▶ Built-in PIM functionality, including scheduler, tasks, memos and calculator.
- ▶ Lots of memory for message and information storage.
- ▶ Choice of alerts including vibration, audio and on-screen.
- ▶ Rechargeable battery (charger included) lasts up to 7 days on one charge.
- ▶ Available in Black or Silver.
- ▶ Optional PC connectivity for data back up and restoring.

## Performance Specifications

RECEIVER	
Frequency Bands	929~942 MHz
Channel Spacing	6.25 kHz, 10 kHz, & 12.5 kHz
Bit Rates	1600, 3200, 6400 bps
Frequency Deviation	± 800 Hz and ± 2400 Hz
Image Rejection	40 dBc, typical
Spurious Rejection	Meets part 15 FCC requirements, 45 dBc, typical
1 MHz Blocking	80 dBc, typical
TRANSMITTER	
Frequency Range	896-902 MHz
Channel Spacing	10 kHz in 6.25 kHz steps
Bit Rates	800, 1600, 6400, & 9600 bps
Signaling	4 level FSK
Frequency Deviation	± 800 Hz and ± 2400 Hz
Emissions	Meets Narrowband PCS FCC part 24D and 90
Power into Antenna	1 Watt typical
Frequency Stability	0.5 PPM
Transmit EIRP	400 mW typical vertically polarized in holster

GENERAL	
Protocol	ReFLEX
Size	4.13 x 2.75 x 0.7 inches (105 x 70 x 18 mm)
Weight	4.23 ounces (120 g)
Memory	2 Mb Flash, 512 Kb SRAM
Battery	Rechargeable 700 mAh Lithium Ion (charger included), lasts up to 7 days on one charge
Viewing area	2.05 x 1.58 inches (52 x 40 mm)
Display	Approximately 7 lines by 25 characters each 4-level gray LCD with EL backlighting
Keypad	34 key QWERTY layout, plus navigation keys and EL backlighting
Operating Temperature	32° ~ 122° F (-10° ~ +50° C)